Global Valves

AD-2000 CE

TA LUFT



Cast Screw Stainless Steel Globe Valves, Threaded Ends - 200 PSI

Cast Screw Steel Globe Valves, Threaded Ends – 200 PSI
KTN, Modentic
Range: DN8-50 - (1/4″-2″)
WORKING PRESSURE : 200 PSI
TEMPERATURE RANGE: -20 to 180 °C




Description

Cast Screw End Globe Valves
1. INVESTMENT CAST COMPONENT
2. RISING STEM
3. SCREW BONNET
5. CONICAL SEAT DESIGN

Technical details

PRODUCT TYPE	Cast Screw Stainless Steel Globe Valves
STANDARD COMPLIANCE	API 602 - BS5352 - ASME B16.34 - API598 - MSS SP-25 - ASME B16.11 ASME B1.20.1
OPERATION	Hand wheel
PRESSURE	200 PSI
CONNECTION	Threaded Ends NPT ***END CONNECTION STANDARD*** ANSI B1.20.1(NPT) / DIN 259 / DIN 2999 / ISO 228 / BSP / PT
PORT	Full Bore
BODY **Material**	ASTM A351 Gr.CF8M
CAP / BONNET **Material**	ASTM A351 Gr.CF8M
STEM **Material**	SS316
DISC **Material**	SS316
SEAT Material	-
BODY SEAL **Material**	PTFE
STEM PACKING **Material**	PTFE



SIZE **NPS**	**E** mm	**H** mm	**L** mm	**WEIGHT** kgs
DN8	70.0	77.0	52.0	0.26
DN10	70.0	77.0	52.0	0.26
DN15	70.0	79.0	52.0	0.26
DN20	70.0	91.0	60.0	0.44
DN25	80.0	105.0	72.0	0.60
DN32	80.0	127.0	81.0	0.96
DN40	90.0	142.0	90.0	1.22
DN50	100.0	158.0	101.0	1.74

SIZE **Inch**	E **Inch**	H **Inch**	L **Inch**	WEIGHT **lbs**
1/4"	2.8	3.0	2.0	0.6
3/8"	2.8	3.0	2.0	0.6
1/2"	2.8	3.1	2.0	0.6
3/4"	2.8	3.6	2.4	1.0
1"	3.1	4.1	2.8	1.3
1-1/4"	3.1	5.0	3.2	2.1
1-1/2"	3.5	5.6	3.5	2.7
2"	3.9	6.2	4.0	3.8

Any kind of business solution or consultation don’t hesitate to

CONTACT US