Gate Valves

AD-2000







CAST STAINLESS STEEL GATE VALVE PN16

CAST STAINLESS STEEL GATE VALVES PN10/16
FLNAGED ENDS
KTN, FERGO
Range: DN15-150 - (1/2″-6″)
PRESSURE : PN10/16
MAX. OPERATING Temp. 450°C



AD-2000

Description

Gate valve DN 100 PN16 stainless steel, flanged connection acc. to EN 1092-1 form B1, face-to-face dimensions acc. to EN 558-1, series 14, body & cover stainless steel (1.4408), wedge made of stainless steel(1.4408), with screwed cover and external stem thread, design acc. to EN 1984, approval: AD2000, NACE, TA Luft, Max. Operating pressure 16 bar, Max. Operating temp. 450°C

Technical details

Bushing/Seats :	**Graphite**
Cover :	Stainless steel (1.4408)
Nominal width :	DN100 - 4'' inch
Spindle :	F316
Connection :	Flange PN10 , Flange PN16
Face to Face length :	EN 558-1 series 14
Body:	Stainless Steel (1.4408)
Actuation :	Handwheel
Max. Operating pressure :	16 bar
Certificate :	TA Air , AD2000
Option:	Full passage
Availability:	In Stock

Any kind of business solution or consultation don't hesitate to

CONTACT US