Global Valves

AD-2000 CE

TA LUFT



FORGED STAINLESS STEEL GLOBE VALVES CLASS 150-1500

FORGED STAINLESS STEEL GLOBE VALVES CLASS 150-1500
FLNAGED ENDS
KTN, Modentic
Range: DN15-50 - (1/2″-2″)
WORKING PRESSURE : CLASS 150-1500
TEMPERATURE ASME B16.34



Description

Features :
Integral flanged valves are available in bonnet
designs. The design is the Bolted Bonnet, With
male-female joint, spiral wound gasket, made in F304L/graphite. Ring joint gasket is also available on request. Integral
flanged end valves are available in gate, globe, piston check design configuration.

Gate valve Design Construction and Specifications :
Integral flanged end vales conform to API602, MSS-SP-118 (as applicable),and ANSI B16.34. BS 5352.
Each are tested according to API 598, Marking is per MSS SP-25.

Construction is as follows :
Full Port or Conventional Port
Face to Face according to ANSI B16.10
Flanges according to ANSI B16.5
Outside Screw and Yoke (OS&Y)
Two piece self-aligning packing gland
Integral backseat
Integral flanges
Bolted bonnet with spiral-wound gasket


TOP TECH

API602 Forged Steel Gate Valves

API602 FGTF-1500 - FULL PORT OR CONVENTIONAL PORT - OUTSIDE SCREW AND YORK - TWO PIECES SELF ALIGNING PACKING GLAND - BOLTED BONNET WITH SPIRAL WOUND GASKET - INTEGRAL BACKSEAT - INTEGRAL FLANGES

Technical details

PRODUCT TYPE	Forged Stainless Steel Globe Valves
STANDARD COMPLIANCE	BS 1873, ASME/ANSI B16.34 Class 150, ASME/ANSI B16.10 Class 150 RF ASME/ANSI B16.10 Class 150 BW, ASME/ANSI B16.5 Class 150 Finish : 125-250 AARH, ASME/ANSI B16.25, API 598
OPERATION	Hand wheel
PRESSURE	CLASS 150-600
CONNECTION	Flanged End ANSI B16.5 / EN1092 *VALVES LENGTH STANDARD* ANSI B16.10 / DIN3202 F1 / F4 / F5
PORT	Full Bore
BODY **Material**	ASTM A182 Gr.F316
CAP / BONNET **Material**	ASTM A182 Gr.F316
STEM **Material**	ASTM A182 Gr.F316
DISC **Material**	ASTM A182 Gr.F316
SEAT Material	-
BODY SEAL **Material**	SS316 + GRAPHITE
STEM PACKING **Material**	FLEXIBLE GRAPHITE
OPTION	Ring joint gasket Forged Carbon Steel Forged Stainless Steel



SIZE **NPS**	**E** mm	**H** mm	**L** mm	**WEIGHT** kgs
DN15	100.0	145.0	140.0	-
DN20	100.0	150.0	152.0	-
DN25	125.0	175.0	165.0	-
DN32	160.0	200.0	178.0	-
DN40	160.0	205.0	190.0	-
DN50	180.0	230.0	216.0	-

++20 122741008. info@toptechparts.net www.toptechparts.net

TOP TECH

SIZE **Inch**	E **Inch**	H **Inch**	L **Inch**	WEIGHT **lbs**
1/2"	3.9	5.7	5.5	-
3/4"	3.9	5.9	6.0	-
1"	4.9	6.9	6.5	-
1-1/4"	6.3	7.9	7.0	-
1-1/2"	6.3	8.1	7.5	-
2"	7.1	9.1	8.5	-

Any kind of business solution or consultation don't hesitate to

CONTACT US

++20 122741008. info@toptechparts.net www.toptechparts.net